

WeatherBLOCKER!

Nano

WeatherBLOCKER! Nano



Technical Data



Pack Size
5 Litres

Application Temperature
10°C - 25°C

Pallet QTY
30 Units

Humidity Requirement
Less than 85%

Application Tool
Brush, Roller or Spray

Suitable Substrate
Concrete, Brick, Stone and Renders

Coverage
Approx 0.1 - 0.2 Litres per M²



Long Term Protection
& Low Maintenance



Energy Saving



WATERPROOF

Waterproofing



Nano Technology



Water Repellent



Highly
Polymer Modified

Permanent, breathable & clear waterproof coating. Protection against the damaging effects of penetrating damp

PRODUCT INFORMATION

WeatherBLOCKER! is an aqueous based hydrophobic impregnating agent based on Fluorocarbon technology. WeatherBLOCKER! is a high quality speciality product for hydrophobic impregnation of natural mineral substrates.

PREPARATION

All surfaces should be clean, reasonably dry and free from algae, lichen & other growths and grease. If there is evidence of organic growth, power wash to remove & apply Wethertex™ Fungicidal wash in accordance with instructions. WeatherBLOCKER! can take up to 7 days until full effects can be visible.

MIXING

WeatherBLOCKER! is supplied ready to use.

APPLICATION

WeatherBLOCKER! is best applied to the mineral substrate by the airless technique, undiluted and in the desired thickness. Brushes or lambskin roller may be used for smaller areas. Up to 0.1 - 0.2 Ltrs/ m² may be applied in one operation to vertical surfaces without loss of material. The exact amount depends on the absorbency of the substrate. Ensure that the substrate is fully saturated.

Wetherby Group

Dalton Industrial Estate, Dalton, North Yorkshire YO7 3HE



WeatherBLOCKER!

Nano

STORAGE

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from date of manufacture.

TOOL CLEANING

All equipment must be washed with clean water immediately after use. Waste material should not be emptied into drainage systems.

HEALTH & SAFETY INSTRUCTIONS

This product contains a biocide for the protection of the cured product. Contains 2-OCTYL-2H-ISOTHIAZOL-3-ONE. May produce an allergic reaction. For further information, please request the material safety data sheet for this product.

IMPORTANT INFORMATION

The weather conditions for application and drying are critical. Do not apply if any of the following conditions are likely to arise during - or in the first 24 hours following application:

- If frost is forecast, or in wet conditions
- When Relative Humidity is above 85%
- In temperatures below +10°C or above +25°C
- If the elevation is in direct sunlight
- If the substrate is hot (at or above 30°C) or below +15°C
- Coverage rates are approx. and do not take into account wastage and uneven substrates

The product must be protected against heavy rain, direct sun or wind in the first 24 hours after application. Sheeting the façade or the scaffold is advised to protect against this. For this particular product if these parameters are not met polymer film damage, wash off and potential failure can occur. It is the responsibility of the application contractor to manage and record the weather conditions during application and curing of the product.

To the best of our knowledge and belief, this information is true and accurate. However, as conditions of use of the product and the expertise of any labour involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application, our tests have been carried out on multiple mineral substrates to create our data however all substrate types are practically impossible to cover so our test results are not exhaustive to all bricks, stone types. No responsibility can be accepted, nor any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that he has consulted our latest literature.



FM 54357

Wetherby Group

Dalton Industrial Estate, Dalton, North Yorkshire YO7 3HE